

CERTIFICATE OF ANALYSIS

IMZ 174

REFERENCE MATERIAL OF STEEL

Analysis listed as percent by weight [% m/m]

C	0.33	Cu	0.17
Si	0.93	Al	0.080
Mn	0.32	V	0.98
P	0.029	Sn	0.010
S	0.023	W	0.021
Cr	5.10	Co	0.011
Ni	0.13	N	0.0288
Mo	1.24		

Certificate Number: IMZ174-081024

Certificate revision history on page 4

Analysis	C	Si	Mn	P	S	Cr	Ni	Mo	
1	0.320	0.895	0.297	0.0270	0.0204	4.933	0.130	1.210	
2	0.321	0.909	0.303	0.0270	0.0206	4.940	0.130	1.215	
3	0.327	0.920	0.310	0.0272	0.0210	5.010	0.131	1.220	
4	0.328	0.923	0.312	0.0290	0.0211	5.025	0.132	1.220	
5	0.330	0.932	0.316	0.0292	0.0220	5.028	0.132	1.228	
6	0.330	0.943	0.318	0.0298	0.0230	5.030	0.133	1.240	
7	0.330	0.950	0.318	0.0310	0.0230	5.092	0.134	1.240	
8	0.335	0.950	0.320	0.0310	0.0230	5.150	0.134	1.240	
9	0.336	0.950	0.320	0.0312	0.0232	5.153	0.137	1.247	
10	0.337	0.953	0.320		0.0233	5.220	0.141	1.250	
11	0.338		0.324		0.0234	5.263		1.270	
12	0.339		0.330		0.0236	5.313			
13	0.341		0.330		0.0239				
14	0.345		0.330		0.0246				
15			0.334						
Average	0.333	0.933	0.319	0.0292	0.0226	5.096	0.133	1.235	
SD	0.007	0.020	0.010	0.0018	0.0013	0.124	0.003	0.018	
Certified	0.33	0.93	0.32	0.029	0.023	5.10	0.13	1.24	
C(95%)	0.004	0.015	0.006	0.0014	0.0008	0.081	0.003	0.012	
Analysis	Cu	Al	V	Sn	W	Co	N	Ti	
1	0.166	0.070	0.933	0.0090	0.0180	0.0090	0.0275	0.0010	
2	0.167	0.075	0.933	0.0090	0.0187	0.0106	0.0277	0.0012	
3	0.170	0.080	0.958	0.0092	0.0206	0.0113	0.0277	0.0017	
4	0.170	0.082	0.970	0.0097	0.0230	0.0127	0.0283		
5	0.170	0.085	0.980	0.0103	0.0233	0.0130	0.0300		
6	0.171	0.085	0.987	0.0117			0.0313		
7	0.172	0.086	0.990						
8	0.173		1.000						
9	0.173		1.000						
10	0.175		1.011						
11	0.176								
12	0.177								
13	0.177								
14	0.180								
Average	0.173	0.080	0.976	0.0098	0.0207	0.0113	0.0288		
SD	0.004	0.006	0.027	0.0010	0.0024	0.0016	0.0016		
Certified	0.17	0.080	0.98	0.010	0.021	0.011	0.0288		
C(95%)	0.002	0.0060	0.021	0.0012	0.0034	0.0023	0.00178		
Analysis	Sb	As	Pb	Bi	Al(sol)				
1	0.0019	0.0071	0.0006	0.0001	0.060				
2	0.0024	0.0083	0.0010		0.064				
3	0.0025		0.0017						
Average									
SD									

$C(95\%) = (t \cdot SD)/\sqrt{n-1}$ - The half-width confidence interval, calculated for the 95 % confidence level, where t is the appropriate Student's t value, SD is the interlaboratory standard deviation and n is the number of acceptable mean values. For further information regarding the confidence interval for the certified value see ISO Guide 35:1989 section 4.

Certification Process: Both preparation of this Reference Material and certification process were prepared according to requirements of ISO Guide 31, ISO Guide 34 and ISO Guide 35. This reference material is in agreement with ISO Guide 30.

Chemical Analysis: Chemical analyses were carried out on chips prepared by milling of the certified portion of the bars and also for some solid samples. Single values in the above table are the means obtained by individual laboratories. The following methods were used for analysis:

C, S	-	high frequency infra-red absorption (HFIR), AES spark;
Mn	-	flame AAS, AES spark, XRF, ICP-AES, photometric, titrimetric;
Si	-	ICP-AES, AES spark, XRF, ICP-AES, photometric, gravimetric;
P	-	ICP-AES, AES spark, XRF, photometric, titrimetric;
Cr	-	flame AAS, AES spark, XRF, ICP-AES, photometric, titrimetric;
Ni	-	flame AAS, AES spark, XRF, ICP-AES, photometric, gravimetric;
Cu, Mo	-	flame AAS, AES spark, XRF, ICP-AES, photometric;
V, W	-	flame AAS, AES spark, XRF, ICP-AES, photometric;
Ti	-	GF AAS, AES spark, ICP-AES;
Al	-	flame AAS, AES spark, ICP-AES, photometric;
Co	-	flame AAS, AES spark, XRF, ICP-AES;
Sn	-	GF AAS, AES spark, ICP-AES;
N	-	high temperature extraction;
As, Sb	-	GF AAS, ICP-AES;
Pb	-	GF AAS, ICP-AES;
Bi	-	GF AAS;
Al (soluble)	-	ICP-AES.

The laboratories participating in the testing of this Reference Material were:

- Alstom Power, Elbląg, Poland
- Ferrostal, Gliwice, Poland
- Huta Lucchini, Warszawa, Poland
- Huta Małapanew, Ozimek, Poland
- Huta Trzyniec, Czech Republic
- Instytut Metalurgii Żelaza, Gliwice, Poland
- ISH Olomouc, Czech Republic
- Laboratorium Aplikacyjne firmy GNR, Italy
- Laboratorium Aplikacyjne firmy LECO, Praga, Czech Republic
- Laboratorium Aplikacyjne firmy Thermo-ARL, Switzerland
- Magnesy Baildon, Katowice, Poland
- Mittal Steel Poland, Oddział Dąbrowa Górnica, Poland
- Mittal Steel Poland, Oddział Kraków, Poland
- US Steel - Labortest, Koszyce, Slovakia

Homogeneity: The homogeneity of this Reference Material was evaluated with the use of statistic parameters obtained during interlaboratory tests in 1996 and found acceptable. Optical emission spectrometry with spark excitation method was used.

Traceability: This Reference Material was tested with the use of optical emission spectrometry with spark excitation and was found compatible to the following CRMs: BS 34D, 36D, 37E and CKD 180-180A.

Production of melt: This material was produced by Huta Baildon, Katowice. The melt was made in an open induction furnace.

Available form: Discs: 40 mm in diameter and 40 mm thick; chips: bottles 100g

Intended use: This Reference Material is intended for use in optical emission and X-ray spectrometric methods (bulks sample) and also in classical wet methods, UV-Vis spectrometry, AAS, ICP-AES, C,S- and N- analyzers and other wet methods (chips).

Caution: In optical emission spectrometry with spark excitation the central part of the surface of discs (approximately 5 mm) should be avoided because of possible segregation of the material.


Validity of certification: The certification of IMZ 174 is valid indefinitely provided this Reference Material is stored in dry place and in environment free from chemical or other aggressive vapours. Periodic recertification is not required. The certification is nullified if this Reference Material is damaged, contaminated or otherwise modified.

Chips: if the contents of the bottle becomes changed (for example oxidized) or contaminated, the whole contents of bottle should be discarded.

Safety: This Reference Material and packing does not contain substances which can directly influence health.

Storage: This Reference Material should be stored in dry place and in environment free from chemical or other aggressive vapours.

Inquiries regarding this Reference Material should be directed to:
rm@git.lukasiewicz.gov.pl

Approved by
Director of the Institute

Prof. Dr. Hab. Eng. Adam Zieliński

Certificate issue date: 08 October 2024

Certificate revision history:

08 October 2024 (editorial changes)

21 January 2021 (change of information regarding validity of certification, editorial changes);
November 2003 (Original certificate date)